




Designer and Manufacturer of Cargo Restraint Systems



## Web Winches

Ancra winches comply with DOT, WSTDA-T3 and Canadian Standard 905 regulations. Available in different base configurations to suit a variety of needs and load requirements.

All winches shown below are right hand models. Left hand models may be available on special orders.  
All winches shown below are bottom mount unless otherwise specified.

Black powder coat finishes are standard on portable and slider winches.



Seamless solid steel mandrel.

Powder coating withstands 250 hours of standard salt spray testing to ensure years of service.

Stamped working load limit and Ancra name certify quality.



**43563-10**

Standard Weld-On  
Weight: 8.6 lbs./3.9 kg.  
WLL: 5,500 lbs./2,500 kg.



**43573-10**

Storable Weld-On  
Weight: 9.1 lbs./4.13 kg.  
WLL: 5,500 lbs./2,500 kg.



**43564-12**

Storable Portable with 2 Set Screws  
Weight: 11.1 lbs./5.0 kg.  
WLL: 5,500 lbs./2,500 kg.



**43564-14**

Standard Portable with 2 Set Screws  
Weight: 10.7 lbs./4.85 kg.  
WLL: 5,500 lbs./2,500 kg.



**43579-20**

Low Profile Side Mount Weld-On  
Weight: 7.3 lbs./3.3 kg.  
WLL: 5,500 lbs./2,500 kg.



**43565-157**

Standard C Track Slider  
Lighter 7mm heat treated frame  
Weight: 7.7 lbs./3.5 kg.  
WLL: 6,000 lbs./2,730 kg.



**43565-127**

Storable C Track Slider  
Lighter 7mm heat treated frame  
Weight: 8.3 lbs./3.8 kg.  
WLL: 6,000 lbs./2,730 kg.



**49207-137**

Standard Double L Track Slider  
Lighter 7mm heat treated frame  
Weight: 6.5 lbs./2.95 kg.  
WLL: 5,500 lbs./2,500 kg.



**49207-187**

Low Profile Double L Track Slider  
Lighter 7mm heat treated frame  
Weight: 6.2 lbs./2.81 kg.  
WLL: 5,500 lbs./2,500 kg.

## Special Application Winches

### Web Winches



**48101-10**

3-Bar Low Profile Side Mount Weld-On  
Weight: 13.3 lbs./6.0 kg.  
WLL: 6,000 lbs./2,730 kg.



**49706-10**

Standard Slider Wilson Track  
Weight: 12.5 lbs./5.7 kg.  
WLL: 5,500 lbs./2,500 kg.



**49246-10-BP**

Standard Slider Utility Trailer Track  
Weight: 13 lbs./5.9 kg.  
WLL: 5,500 lbs./2,500 kg.



**41681-10**

Standard Combination Weld-On  
Weight: 10.6 lbs./4.8 kg.  
WLL: 5,500 lbs./2,500 kg.

### Combo Winch

## SilverCap OverDrive Ratcheting Cap

PATENTED

Convert any winch into a ratcheting winch by adding Ancra's OverDrive Ratcheting Cap. The lubricated cap with a Grime Guard Weather-Tight Seal fits over the existing winch cap without having to remove the winch from the trailer, making it faster and safer than conventional winches.



**SilverCap OverDrive**  
Turns Any Winch Into A Ratcheting Winch



**49723-10**

Weight: 3.45 lbs./1.56 kg.





## Winch Track

For standard C track and Double L track slider winches



**42357-11**  
**Steel C Track** - Formed from high strength 1/4" steel plate  
 Weight: 39 lbs./17.73 kg.  
 Length: 6'



**42357-21**  
**Aluminum C Track** - High strength aluminum extrusion  
 Weight: 19 lbs./8.64 kg.  
 Length: 6'



**49242-10-120**  
**Aluminum Double L Track** - Designed for Double L slider winches. Weight: 26.25 lbs./11.92 kg. Length: 10'

## PortaWinch

**Versatile solution to turn stake pockets into anchoring points on flatbed trailers**

**PORTAWINCH™** (3-Bar Style) **PATENTED**



**49716-10**  
 Standard outward off-set  
 Weight: 11.5 lbs./5.2 kg.  
 WLL: 5,500 lbs./2,500 kg.

**49716-11**  
 Inward off-set for track-mounted tarp clearance.  
 Weight: 11.5 lbs./5.2 kg.  
 WLL: 5,500 lbs./2,500 kg.

**Covered by multiple U.S. and International Patents.**

## Ergo 360 Winch Bars

Easily rotates to any angle to provide the leverage needed to tension a strap



The Ergo 360 Bar is simply a better alternative to standard winch bars. The ergonomic design keeps the handle and tip in parallel alignment and in your "Power Zone" making it safer and easier to use. Available in 3 models standard, combination, and combination box end.



**50015-10**  
**Standard Ergo Bar, 34"**, Painted, Weight: 5.0 lbs./2.27 kg.



**50015-20**  
**Combination Ergo Bar, 34"**, Painted, Weight: 6.5 lbs./2.95 kg.



**50015-21**  
**Combination Box End Ergo Bar, 38-5/8"**, Painted, Weight: 6.0 lbs./2.72 kg.

## Winch Bars

Tapered and angled at the end for easy operation, Ancra's winch bar handles are knurled at two sections, and the mushroom tip helps keep the bar from slipping from the winch cap. They are heat-treated for extra strength and cycle tested to simulate years of heavy use. Combination winch bars can be used to release tension on chain binders. Use caution to avoid injury. Not to be used as a cheater bar.



*Flanged mushroom tip helps keep the bar from slipping from the winch cap.*



**42313-10**  
**Standard Painted**, Weight: 5.0 lbs./2.27 kg.



**42313-12**  
**Combination Box End**, Painted Silver and Yellow, Weight: 6.5 lbs./2.95 kg.



**42313-19**  
**Combination Chrome**, Weight: 6.5 lbs./2.95 kg.



**42313-17**  
**Standard Chrome**, Weight: 5.0 lbs./2.27 kg.



## Standard 2" Winch Strap WLL: 3,333 lbs./1,515 kg.



**41659-10-27**  
27-ft. with Flat Hook

**41659-10-30**  
30-ft. with Flat Hook



**41659-13-27**  
27-ft. with Wire Hook

**41659-13-30**  
30-ft. with Wire Hook

## Standard 3" Winch Strap WLL: 5,400 lbs./2,450 kg.



**41660-10-27**  
27-ft. with Flat Hook

**41660-10-30**  
30-ft. with Flat Hook



**41660-14-27**  
27-ft. with Chain Anchor

**41660-14-30**  
30-ft. with Chain Anchor

## Standard 4" Winch Strap WLL: 5,400 lbs./2,450 kg.



**43795-10-27**  
27-ft. with Flat Hook

**43795-10-30**  
30-ft. with Flat Hook



**43795-11-27**  
27-ft. with Delta Ring

**43795-11-30**  
30-ft. with Delta Ring



**43795-13-30**  
30-ft. with Twisted Loop



**43795-15-27**  
27-ft. with Chain Anchor

**43795-15-30**  
30-ft. with Chain Anchor

## Premium 4" X-TREME Winch Strap WLL: 5,400 lbs./2,450 kg.

Delivers greater abrasion resistance over conventional web straps

**The ultimate winch straps for extreme applications. Ancra's new X-TREME webbing delivers greater durability, strength and abrasion resistance. Testing shows 80% retained strength over standard webbing.**



**43795-91-30**  
30-ft. with Delta Ring



**43795-90-27**  
27-ft. with Flat Hook

**43795-90-30**  
30-ft. with Flat Hook



**43795-95-30**  
30-ft. with Chain Anchor



## Roll-On/Roll-Off Container Strap 4" x 5-ft. with Container Hook-FMCSA Compliant



**49526-10**

4-in. x 5-ft. Strap w/ 48968-11 Container Hook.  
WLL: 5,400 lbs./2,450 kg.



**49526-11**

4-in. x 5-ft. Strap w/ 48968-11 Container Hook and Sewn Loop end.  
WLL: 5,400 lbs./2,450 kg.

## Coil Racks Available in both light duty and heavy duty models for your specific applications



**49344-10**

Light Duty, 10 gauge steel, Weight: 5.7 lbs./2.60 kg.



**49344-12**

Heavy Duty, 1/4 steel sheet per ASTM A36, Weight: 15.63 lbs./7.09 kg.

## Transport Chain

Grade 70 Transport Chain meets NACM standards

### Chain Assemblies with Clevis Hooks



#### 5/16" Chain Assemblies

**45881-10-16** 5/16" x 16" WLL: 4,700 lbs.

**45881-10-20** 5/16" x 20" WLL: 4,700 lbs.

**45881-10-25** 5/16" x 25" WLL: 4,700 lbs.

#### 3/8" Chain Assemblies

**45881-11-16** 3/8" x 16" WLL: 6,600 lbs.

**45881-11-20** 3/8" x 20" WLL: 6,600 lbs.

**45881-11-25** 3/8" x 25" WLL: 6,600 lbs.

#### 1/2" Chain Assemblies

**45881-13-20** 1/2" x 20" WLL: 11,300 lbs.

**45881-13-25** 1/2" x 25" WLL: 11,300 lbs.

### Bulk Chain/Clevis Hooks



#### 5/16" Chain x 400'

**45880-10** Wt: 408 lbs.

#### 3/8" Chain x 200'

**45880-11** Wt: 296 lbs.

#### 1/2" Chain x 100'

**45880-13** Wt: 251 lbs.

#### 1/4" Chain x 400'

**45880-12** Wt: 262 lbs.



#### 5/16" Clevis Hook

**45946-10** Wt: .85 lbs.

#### 3/8" Clevis Hook

**45946-11** Wt: 1.10 lbs.

#### 1/2" Clevis Hook

**45946-13** Wt: 2.10 lbs.

#### 1/4" Clevis Hook

**45946-12** Wt: .40 lbs.

## Load Binders Drop forged steel meeting FMCSA and DOT specifications. In three popular models.

### Lever Load Binders



**45943-10**

Accepts 5/16"-3/8" Chain  
WLL: 5,400 lbs. Wt. 7.9 lbs.

**45943-10HD** HEAVY DUTY

Accepts 5/16"-3/8" Grade 70 Chain  
WLL: 6,600 lbs. Wt. 9.4 lbs.

**45943-11**

Accepts 3/8"-1/2" Chain  
WLL: 9,200 lbs. Wt. 11.9 lbs.

**45943-13**

Accepts 1/2"-5/8" Chain  
WLL: 13,000 lbs. Wt. 20.8 lbs.

**45943-12**

Accepts 1/4"-5/16" Chain  
WLL: 2,600 lbs. Wt. 3.5 lbs.

### Recoilless Lever Load Binder



**45943-14**

Accepts 5/16"-3/8" Chain  
WLL: 5,400 lbs. Wt. 9.0 lbs.

### Lever Binder Locking Clip



**50117-10**

Securely Holds Binder Handle  
Weight: .40 lbs./0.18 kg.

### Ratchet Load Binders



**45943-20**

Accepts 5/16"-3/8" Chain  
WLL: 5,400 lbs. Wt. 10.4 lbs.

**45943-20HD** HEAVY DUTY

Accepts 5/16"-3/8" Grade 70 Chain  
WLL: 6,600 lbs. Wt. 10.5 lbs.

**45943-21**

Accepts 3/8"-1/2" Chain  
WLL: 9,200 lbs. Wt. 11.8 lbs.

**45943-23**

Accepts 1/2"-5/8" Chain  
WLL: 13,000 lbs. Wt. 15.7 lbs.

**45943-22**

Accepts 1/4"-5/16" Chain  
WLL: 2,600 lbs. Wt. 3.57 lbs.

## Ratchet Strap Assemblies Meets DOT and WSTDA T-1 standards for synthetic web tiedowns

**2" Long-Wide Handle Ratchet Buckle Straps WLL: 3,333 lbs./1,515 kg.**



**45982-10**  
27-ft. with Flat Hooks

**45982-11**  
30-ft. with Flat Hooks



**45982-15**  
27-ft. with Chain Anchor

**45982-34**  
30-ft. with Chain Anchor



**45982-42**  
27-ft. with Wire Hooks

**45982-43**  
30-ft. with Wire Hooks



**45982-19**  
27-ft. with Twisted Snap Hooks

**45982-36**  
30-ft. with Twisted Snap Hooks

### 3" Ratchet Buckle Straps WLL: 5,400 lbs./2,450 kg.



**48987-20**  
27-ft. with Flat Hooks

**48987-21**  
30-ft. with Flat Hooks



**48987-24**  
27-ft. with Chain Anchor

**48987-25**  
30-ft. with Chain Anchor

### 4" Ratchet Buckle Straps WLL: 5,400 lbs./2,450 kg.



**49346-10**  
27-ft. with Flat Hooks

**49346-11**  
30-ft. with Flat Hooks



**49346-14**  
27-ft. with Chain Anchor

**49346-15**  
30-ft. with Chain Anchor

## Corner Protectors Full line of corner protectors to protect your straps and cargo



**42098-11**  
**Fiber Reinforced Rubber** - For use with up to 3" web straps  
Weight: .63 lb./ .29 kg.



**42098-12**  
**Fiber Reinforced Rubber** - For use with up to 4" web straps  
Weight: .75 lb./ .34 kg.



**49584-10**  
**12" Plastic** - For use with up to 4" web straps  
Weight: .47 lb./ .21 kg.



**49377-10**  
**Steel** - For use with chain  
Weight: 1.10 lbs./ .50 kg.



**49577-10**  
**Steel** - For use with chain  
Weight: .90 lb./ .41 kg.



**49756-10**  
**Steel** - For use with chain and straps  
Weight: 1.26 lbs./ .57 kg.



**49377-11**  
**Rubber Coated Steel**  
For use with chain and extends 4" to protect load.  
Weight: 1.9 lbs./ .86 kg.



**41516-11**  
**Aluminum 6061-T6**  
Suitable for 2" webbing.  
Weight: .63 lbs./ .29 kg.



**43986-10**  
**High Density Polymer** - For up to 4" web straps  
Weight: .06 lb./ .03 kg.



**49913-10**  
**Tarp Protector**  
Yellow plastic.  
Weight: .21 lb./ .09 kg.

**BE SURE YOU'RE SECURED** If any part of the load securement system is loose — even if the required number of straps are used per regulation but are not tensioned properly — the load is considered unsecured. It is your responsibility to ensure the cargo is secure.



## Ancra X-TREME - Engineered for Strength And Durability

Ancra Ratchet Buckle Strap Assemblies have redefined the industry standard. Now with the tested and proven 80% retained strength of Ancra X-TREME webbing and the integrity of our ratchet buckles, these assemblies surpass the others. A complete line of Ancra's standard and heavy-duty assemblies and accessories can meet all your specific requirements.

- Custom lengths and a wide range of end hardware are available
- Complies with WSTDA T-1 Standards
- Webbing meets or exceeds WSTDA T-4 Standards
- Standard fixed end length is 18-in., unless otherwise specified



### Premium 2" X-TREME Ratchet Straps WLL: 3,333 lbs./1,515 kg.




**45982-90-27**  
27-ft. with Flat Hooks



**45982-90-30**  
30-ft. with Flat Hooks




**45982-93-30**  
30-ft. with Chain Anchors



**45982-95-27**  
27-ft. with Wire Hooks



**45982-95-30**  
30-ft. with Wire Hooks



**45982-90-27-WK**  
27-ft. Web Keeper with Flat Hooks



**45982-90-30-WK**  
30-ft. Web Keeper with Flat Hooks

### Premium 3" X-TREME Ratchet Straps WLL: 5,400 lbs./2,450 kg.



**48987-90-27**  
27-ft. with Flat Hooks



**48987-90-30**  
30-ft. with Flat Hook



**48987-92-27**  
27-ft. with Chain Anchors



**48987-92-30**  
30-ft. with Chain Anchors

### Premium 4" X-TREME Ratchet Straps WLL: 5,400 lbs./2,450 kg.



**49346-90-27**  
27-ft. with Flat Hooks



**49346-90-30**  
30-ft. with Flat Hooks



**49346-91-27**  
27-ft. with Chain Anchors



**49346-91-30**  
30-ft. with Chain Anchors



**49346-93-27**  
27-ft. with Wire Hooks



**49346-93-30**  
30-ft. with Wire Hooks

# Top Premium Brand Tarp Ties

Made in USA 

Made in the USA and known for quality, durability, and resistance to weather, these tarp ties offer good stretch recovery and maintain their strength over the entire life of the tarp ties. The three lines include the longest lasting, larger cross section Goldline EPDM tarp ties best recognized by truckers, and the smaller cross section Silverline Elite™ EPDM, and Silverline natural rubber tarp ties. They all offer exceptional strength and costs that compete with import tarp ties. All hooks are made in the USA from wire coils.

**Truckers Choice  
for Over 40 Years!**



- Quantity 50 per box
- Designed to hold tarp covers on trucks and trailers
- Not to be used to restrain or secure cargo
- Wear safety glasses and use caution when using tarp ties
- Molded EPDM construction for high Ozone resistance and strength resiliency or molded natural rubber for good cold weather stretch properties

**GOLDLINE®**

**SILVERLINE®  
ELITE  
EPDM**

**SILVERLINE®**

**52210GL**

10" Goldline HD EPDM

**52215GL**

15" Goldline HD EPDM

**52221GL**

21" Goldline HD EPDM

**52231GL**

31" Goldline HD EPDM

**52241GL**

41" Goldline HD EPDM

**52210SE**

10" Silverline Elite EPDM

**52215SE**

15" Silverline Elite EPDM

**52221SE**

21" Silverline Elite EPDM

**52231SE**

31" Silverline Elite EPDM

**52241SE**

41" Silverline Elite EPDM

**52210**

10" Silverline Natural Rubber

**52215**

15" Silverline Natural Rubber

**52221**

21" Silverline Natural Rubber

**52231**

31" Silverline Natural Rubber

**52241**

41" Silverline Natural Rubber

## X-TREME GUARD™

Ankra's new high-density polyethylene X-TREME GUARD™ Corner Protector distributes strap tension over the length of the guard to prevent your cargo from being crushed by the straps and protects your webbing from cuts and abrasion. Made in lengths of 12-, 24-, 36- and 48-inches, this durable guard is strong yet lightweight, and crack/ weather resistant to -30°.

- Constructed of High Density Polyethylene for strength and durability
- Protect cargo from being crushed by the straps and the webbing from cuts and abrasion
- Spread the strap tension over the length of the guard
- More durable than wood and greater memory than aluminum
- Weather and UV resistant, Good to -30°F
- Made from recycled materials



**50089-12**  
8" x 1' long  
Weight: .8 lbs./0.36 kg.



**50089-24**  
8" x 2' long  
Weight: 1.7 lbs./0.78 kg.



**50089-36**  
8" x 3' long  
Weight: 2.7 lbs./1.23 kg.



**50089-48**  
8" x 4' long  
Weight: 3.6 lbs./1.63 kg.





## Flags & Banners Meets FMCSA 393.87 Standards



**49894-10**

Wide Load/Oversize Load, 2-sided,  
84" x 18" Vinyl  
Yellow with four 44" ropes & grommets

**49894-12**

Wide Load/Oversize Load, 2-sided,  
72" x 14" Vinyl  
Yellow with four 44" ropes & grommets



**49894-11**

Wide Load/Oversize Load, 2-sided,  
84" x 18" Vinyl  
Yellow with four grommets, Sewn in Ropes,  
Top and Bottom



**49894-13**

Oversize Load Mesh Sign, Single Sided  
84" x 18" Polyester  
Yellow with 4 grommets and four 44" ropes

**49894-14**

Wide Load Mesh Sign, Single Sided  
84" x 18" Polyester  
Yellow with 4 grommets and four 44" ropes



**49895-10**

Canadian "D" Sign  
96" x 12"  
Red/White Vinyl  
10 Grommets



**49893-10**

Flourescent Red Safety Flag  
18" x 18"  
Heavy Duty Mesh  
Wooden dowel



**49893-11**

Red Safety Flag  
18" x 18"  
Cotton  
Steel wire rod



**49893-12 49893-14**


Flourescent Red (-12) or Orange (-14)  
Safety Flag  
18" x 18"  
Heavy Duty Mesh  
2 brass grommets



**49893-13**

Flourescent Orange  
Safety Flag  
18" x 18"  
Heavy Duty Mesh  
Wooden dowel

## Web Winders Rolls all your winch straps neatly and quickly. Helps to extend the life of your winch straps.



**50092-10**

EZ Winder Strap Winder quickly and easily  
winds webbing onto your winch for storage.



**45801-10**

Web Winder. Constructed of all steel, the Ankra  
Web Winder winds 2-in., 3-in. and 4-in. winch  
straps for compact storage. Easy to attach to  
vehicle rails, easy to remove with tapered forks,  
and easy to disassemble for storage.  
Weight: 3.25 lbs./1.48 kg.



## Lift-Deck

THE DECK SYSTEM SPECIALISTS

## Decking System


PATENTED

U.S. Patent No. 6,074,143

The most popular patented solution for decking loads in trailer and van bodies. With Ancra's patented adjustable second deck in your trailer, you can carry double the amount of palletized freight, or you can mix loads with only part of the vehicle double decked. The Ancra Lift-A-Deck® II system is the most versatile you can install. With many track styles to choose from, installations can be made on any type of vehicle construction.



### Standard & Low Profile Beams w/ Low Profile Foot and Channel Assembly



**49414-15**

Standard LAD Beam  
Adjustment range: 95.1" - 105.6"  
Weight: 18.1 lbs./8.2 kg.  
Decking WLL: 2,200 lbs./999 kg.\*  
Shoring WLL: 2,200 lbs./999 kg.

**49414-19**

Heavy Duty LAD Beam  
Adjustment range: 95.1" - 105.6"  
Weight: 19.7 lbs./8.9 kg.  
Decking WLL: 3,000 lbs./1,360 kg.  
Shoring WLL: 2,500 lbs./1,135 kg.\*

### Wide Top Beam w/ Low Profile Foot and Channel Assembly

The textured Beam top surface is 4-1/2" wide to increase the contact area for cargo on the beam deck.



**50080-11**

Wide Top LAD Beam Assembly  
Adjustment range 95.1" - 105.6" / Weight: 24.9 lbs./11.3 kg.  
Decking WLL: 4,000 lbs./1,816 kg.\* Not recommended for shoring.

PATENTED



### Poly Deck Board

- Lighter than plywood - Increase trailer capacity
- Ergonomic - Convenient hand slot
- Stackable - Nests for storage
- Durable - Reduces purchase frequency
- Recyclable - Energy savings



**50105-11**

For beams set at 16" & 24" centers.  
48" x 48" x 2.7"H / Weight: 21 lbs./9.53 kg.

### Lift-A-Deck II Track Options - Other Track Styles Available



**50072-14-72.00**


Flanged Double Track



**50058-18-72.00**

Flanged Single Track

### Beam Release Bar



**49445-12**

Weight: 2.5 lbs./1.14 kg.

### Lift-A-Deck II Logistic Straps



12-ft. 16-ft. 20-ft.  
**40602-100 40602-101 40602-102**

6,000 lb. Polyester Webbing with Cam Buckle and Single Stud Fitting.  
Working Load Limit: 833 lbs./378 kg.



12-ft. 16-ft. 20-ft.  
**48672-16 48672-17 48672-18**

6,000 lb. Polyester Webbing with Ratchet Buckle and Double Stud Fitting. Fixed End: 48-in.  
Working Load Limit: 1,500 lbs./680 kg.

### Beam Release Bar Holder



**50055-10**

Weight: .44 lbs./0.2 kg.



## Logistic Track

Ankra Series E, A and F Track were designed to team with Ankra end fittings, Beam Sockets, and Decking/Shoring Beams for the strongest, most reliable support. Steel constructed and tested for strength, Ankra Track comes in 10 ft. (3 m) lengths for a wide range of cargo restraint applications. To withstand corrosion, Ankra galvanized track has a G-90 hot dip finish with a surface chemical treatment.

### Series E Logistic Track - Made with high grade 12-gauge steel



**48117-25-120.00**


**Gray Powdercoat**

Weight: 16.6 lbs./7.5 kg.  
Length: 10-ft./3 m

**48117-25-60.00**

**Gray Powdercoat**

Weight: 8.3 lbs./3.77 kg.  
Length: 5 ft./1.5 m



**48117-21-120.00**

**Galvanized**

Weight: 17.2 lbs./7.80 kg.  
Length: 10-ft./3 m

**48117-21-60.00**

**Galvanized**

Weight: 8.6 lbs./3.90 kg.  
Length: 5-ft./1.5 m



**48117-32-120.00**

**Black Powdercoat**

Weight: 16.6 lbs./7.5 kg., Length: 10-ft./3 m

#### Vertical

**40838-10**


**Gray Powdercoat**

Weight: 13.5 lbs./6.1 kg.  
Length: 10-ft./3 m


**40838-11**

**Galvanized**

Weight: 14 lbs./6.4 kg.  
Length: 10-ft./3 m



### Series F Logistic Track



**40849-14**

**Galvanized** 1.62 in. hole spacing & 3/4" hole dia.  
Weight: 6.0 lbs./2.7 kg., Length: 10 ft./3 m. 15-gauge.



**49313-13**

**Galvanized** 1.62 in. hole spacing.  
Weight: 12.2 lbs./5.53 kg., Length: 10 ft./3 m. 12-gauge.

### Series A Logistic Track



**42948-10**

**Gray Powdercoat**

Weight: 15.0 lbs./6.8 kg., Length: 10-ft./3 m. 12-gauge.



**49359-10**

**Aluminum**

Weight: 8 lbs./3.6 kg., Length: 10 ft./3 m.

### Shoring Bars – F Series with new easy push button design

#### Round Shoring Bar



#### Square Shoring Bar



Adjustable in 2-in. increments with recommended install length of 81-117 in.



**49439-10**

For 3/4-in. hole diameter track (U.S.)  
Shoring WLL: 500 lbs./227 kg., Wt: 20.0 lbs./9.1 kg.

**49439-11**

For 1-in. hole diameter track (Canada)  
Shoring WLL: 500 lbs./227 kg., Wt: 20.0 lbs./9.1 kg.



**49439-20**

For 3/4-in. hole diameter track (U.S.)  
Shoring WLL: 1,000 lbs./454 kg., Wt: 28.0 lbs./12.71 kg.

**49439-21**

For 1-in. hole diameter track (Canada)  
Shoring WLL: 1,000 lbs./454 kg., Wt: 28.0 lbs./12.71 kg.



## Series E and A Decking/Shoring Beams with Patented Flat Latch

**PATENTED** U.S. Patent No. 6,895,867

All Ankra Decking/Shoring Beams are equipped with our patented Flat Latch. The Flat Latch eliminates bent triggers, jammed beams, costly beam replacement and repairs, and out-of-service problems. The Flat Latch can't damage interior trailer walls. The flat latch channel assembly can be purchased separately to retro-fit older trigger style beams.



### Standard Duty Aluminum E and A Decking Beams - Decking & Shoring WLL: 2,200 lbs.

- 43638-50** Adjustment range 85.7-96.6 in. Wt: 16.0 lbs./7.27 kg.
- 43638-51** Adjustment range 92.9-103.6 in. Wt: 18.8 lbs./8.55 kg.

### Heavy Duty Aluminum E and A Decking Beams - Decking WLL: 3,000 lbs. Shoring WLL: 2,500 lbs.

- 49039-50** Adjustment range 84.7-95.6 in. Wt: 20.5 lbs./9.32 kg.
- 49039-51** Adjustment range 92.9-103.6 in. Wt: 22.5 lbs./10.23 kg.
- 49039-52** Adjustment range 96.0-106.9 in. Wt: 24.25 lbs./11.03 kg.

## Cargo Sta Load Bars - Available in Aluminum and Steel Bar models for light to medium duty applications. Bolt-On Feet



### Aluminum Cargo Sta

- 43782-15** 6061 T6 Aluminum, Length/Weight: 89.75 - 104.5 in. 8.95 lbs./4.07 kg. Long Tube Diameter: 1.50 in.

### Steel Cargo Sta

- 48407-10** Galvanized Steel Tubing, Length/Weight: 89.75 - 104.5 in. 11.72 lbs./5.33 kg. Long Tube Diameter: 1.50 in.

## Jack Bars - Ankra's jack mechanism makes quick work of securing loads and is available in three models for light to medium duty applications.




### Heavy Duty One-Piece - Galvanized finish for corrosion resistance.

- 49205-25** Weight: 16.2 lbs./7.35 kg. Adjustment range: 85.0" - 104.0" Black Handle
- 49205-26** Weight: 16.6 lbs./7.54 kg. Adjustment range: 85.0" - 114.0" Red Handle

## Heavy-Duty One-Piece Jack Bar with Hoops -

Built-in hoops for restraining small items and packages. One-Piece Galvanized



### 49205-27

Weight: 20.0 lbs./9.08 kg. Adjustment range: 85.0" - 114.0" Red Handle

### 49205-28

Weight: 19.6 lbs./9.0 kg. Adjustment range: 85.0" - 104.0" Black Handle


## Universal Jack Bar - This jack bar features a patented design which allows for 3 adjustment range settings, increasing its versatility for use in half load applications.



- 49205-31** Adjustment range- Fully extended: 85-114-in. Mid extension: 70-99-in. Fully retracted: 51-80-in. Weight: 18.2 lbs./8.26 kg. **PATENTED** U.S. Patent No. 6,736,371.



## Accessories



**43991-10**

### Cargo Sta Hoop Set

Designed to help restrain the movement of small packages of cargo within your truck or trailer. For 43782 and 48407 round tube bars. Tube Diameter: 1.5 in. Weight: 10.0 lbs./4.5 kg.



**49348-11**

### Bar Keep Cargo Bar Holder

Constructed of high quality steel and finished with black powder coating for corrosion resistance. Holds two standard or heavy-duty cargo bars. Weight: 6.68 lbs./3.03 kg.



**40921-10**

### Standard Beam Socket


For use w/ commercial grade Douglas Fir 2"x6" lumber. Weight: .70 lb./32 kg.



**40921-11**

### Heavy-Duty Beam Socket

For use w/ commercial grade Douglas Fir 2"x6" lumber. Internally welded plate for added strength. Weight: .85 lb./39 kg.



**43627-13**

### Replacement Channel Assembly

With patented flat latch. 11 Gauge. For aluminum beams 43638, 49039 and 50158. Weight: 3.8 lbs./1.73 kg.



**40386-11**

### Series E/A Rope Tie Off

With spring actuated fitting for rope use in Series E or A track. WLL: 1,333lbs./605 kg. Weight: .40 lbs./18 kg.



**49015-18**

18-in. Weight: .20 lb./09 kg

**49015-24**

24-in. Weight: .30 lb./14 kg.

**49015-36**

36-in. Weight: .30 lb./14 kg.

### Door Pull Straps

Rust protected galvanized steel clip is pre-punched for easy installation. For pulling overhead doors, side doors, and wheeled carts.

## Series E Cam Buckle Straps with Spring End Fittings

Popular straps for securing light to medium loads. Comes in 3 color coded sizes. WLL: 833 lbs./378 kg.



**40602-17**

12-ft, - Yellow Webbing. Weight: 1.65 lbs.



**40602-18**

16-ft, - Gray Webbing. Weight: 1.80 lbs.



**40602-19**

20-ft, - Blue Webbing. Weight: 1.95 lbs.

## Series E Ratchet Buckle Straps with Spring End Fittings

Low profile ratchet buckle makes tensioning more convenient for securing loads. Three standard color coded sizes. WLL: 1,333 lbs./605 kg.



**48672-13**

12-ft, - Yellow Webbing. Weight: 2.25 lbs.



**48672-14**

16-ft, - Gray Webbing. Weight: 2.40 lbs.



**48672-15**

20-ft, - Blue Webbing. Weight: 2.55 lbs.

## Torque Limiting Ratchet Straps with Spring End Fittings

Reduces the possibility of damage to logistics track and sidewalls by limiting the pre-load torque placed on the strap assembly. Patented ratchet mechanism limits strap tension to 300 lbs., enough to secure your load, but not enough to cause damage from over tightening. WLL: 1,333 lbs./605 kg



**48672-33**

12-ft, - Yellow Webbing. Weight: 2.50 lbs.



**48672-34**

16-ft, - Gray Webbing. Weight: 2.65 lbs.



**48672-35**

20-ft, - Blue Webbing. Weight: 2.80 lbs.



## Utility Tiedowns – Versatile and reliable for securing a wide range of light- to medium-duty cargo.



**41048-10**  
**Cam Buckle Tiedown**  
1" x 5-1/2' Red  
Vinyl Coated S Hooks  
Fixed End: 6-in.  
WLL: 400 lbs./181 kg.  
Weight: 1.60 lbs./.73 kg.



**43887-10**  
**Mini Ratchet Strap with D-Ring and Wire Hooks**  
WLL: 1,000 lbs./454 kg.  
1" x 16'  
Weight: 1.56 lbs./.71 kg.  
**43887-11** 1" x 20'  
Weight: 1.69 lbs./.77 kg.



**49368-10**  
**Ratcheting Tiedowns**  
1" x 15' 4-pack  
1" red Ratchet strap with vinyl-coated S Hooks secures cargo, equipment and household furnishings.  
Weight: 4.7 lbs./2.14 kg.  
WLL: 266 lbs./121 kg.



**49368-11**  
**Cam Buckle Tiedowns**  
1" x 6' 4-pack  
1" black Cam strap with scratch-resistant vinyl-coated S Hooks. A simple way to secure your possessions.  
Weight: 3.7 lbs./1.69 kg.  
WLL: 266 lbs./121 kg.



**49368-12**  
**Combo 4 Pack**  
Contains two each 1" multipurpose Ratchet and Cam Buckle tie downs with scratch-resistant vinyl coating.  
Weight: 4.2 lbs./1.91 kg.  
WLL: 266 lbs./121 kg.



**95002**  
**Ratcheting Tiedowns**  
1" x 10' 2-pack  
1" black Ratchet straps with vinyl-coated S Hooks in an interactive package.  
Weight: 2.25 lbs./1.0 kg.  
WLL: 550 lbs./250 kg.



**95007**  
**Ratcheting Tiedowns**  
1" x 12' Endless Loop, 2-pack, 1" Ratchet straps in an interactive package.  
Weight: 1.75 lbs./.79 kg.  
WLL: 550 lbs./250 kg.



**95003**  
**Retractable Ratcheting Tiedowns**  
1" x 6' 2-pack  
1" black Retractable Ratchet straps with scratch-resistant vinyl-coated S Hooks in an interactive package.  
Weight: 3.20 lbs./1.45 kg.  
WLL: 500 lbs./227 kg.



**95004**  
**Cam Buckle Tiedowns**  
1" x 8' 4-pack  
1" red Cam straps with scratch resistant vinyl-coated S Hooks in an interactive package.  
Weight: 3.8 lbs./1.72 kg.  
WLL: 400 lbs./180 kg.



**95005**  
**Ratcheting Tiedowns**  
1" x 10' 4-pack  
1" black Ratchet straps with vinyl-coated S Hooks in an interactive package.  
Weight: 4.6 lbs./2.1 kg.  
WLL: 550 lbs./250 kg.



**49603-10**  
**TrackStar Motorcycle Wheelchock**  
Quick Connect to aircraft style L track. Fits tire widths from 3.5" to 5.5". Comes complete with mounting kit.  
Weight: 7.0 lbs./3.18 kg.



## Specifications


### Working Load Limit (WLL)

The maximum load a component or assembly should be subjected to during routine use.

### Rated Load Capacity

Ratings are generally established and/or regulated by industry or legislative standards and may vary from industry to industry. The working load limit rating (WLL) is established by Federal DOT Standards at 1/3 of the Breaking Strength of the assembly.

*Note: All strengths referenced in this brochure unless noted, are based on a straight pull application.*



### IMPORTANT NOTE:

It is the owner's and user's responsibility to determine suitability of a product for any particular use. Check all applicable industry, trade association, federal, state and local regulations. Read all operating instructions and warnings carefully.

All ratings shown in this catalog are based on the product being new, and used in normal environmental conditions. Special consideration must be given to item selection when unusual conditions can be expected. Particular caution should be exercised to avoid exposing the product to sharp edges, acids, alkalis and temperatures above 194°F.

Products are subjected to age, wear, and deterioration, all of which cause a reduction in the product's working load limit. We recommend that all products be regularly inspected. Any worn, deformed, misused or overloaded products should be replaced.

**CAUTION!** The component with the lowest working load capacity in the entire restraint system will determine its strength. Each component of the entire system plays an important part in restraining cargo. It is important that tie downs be attached to anchorage that are of sufficient strength to properly secure the load. For example, if one anchors a standard web binder assembly with a rated WLL of 5,000 lbs. to a device with a WLL of 1,000 lbs., then that system is only as good as the anchorage and would be limited to a 1,000 lbs. capacity WLL.

The purpose of this catalog is to assist our customers in the selection of cargo restraint products suitable for their specific applications. Because we continuously strive to offer new and improved products, part numbers and specifications are subject to change without notice. Please contact your Ancra Representative or our Customer Service Department for any new information.

## WARRANTY

All Ancra International LLC products, unless otherwise indicated are warranted to be free from defect in material or workmanship for a period of six (6) months from date of shipment. During this period, Ancra International LLC will, at its option repair or replace without charge any products or part thereof found to be defective in material or workmanship. This warranty does not extend to any product which has been subject to misuse, abuse, negligence, accident, alteration or repair.

All Ancra International LLC SilverCap OverDrive product, unless otherwise indicated are warranted to be free from defect in material or workmanship for a period of twelve (12) months from date of shipment. During this period, Ancra International LLC will, at its option repair or replace without charge any product or part thereof found to be defective in material or workmanship. This warranty does not extend to any product which has been subject to misuse, abuse, negligence, accident, alteration or repair.

Ancra International LLC LAD II & or RAR systems, unless otherwise indicated are warranted to be free from defect in material or workmanship for a period of twenty (24) months from date of shipment. During this period, Ancra International LLC will, at its option repair or replace without charge any product or part thereof found to be defective in material or workmanship. This warranty does not extend to any product which has been subject to misuse, abuse, negligence, accident, alteration or repair.

Defective products must be returned to Ancra International LLC within the above period, transportation prepaid. Ancra will bear the cost of return transportation. Contact Customer Service for details.


THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES EXPRESSED OR IMPLIED INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE. IN NO EVENT WILL ANCRA INTERNATIONAL LLC BE LIABLE FOR SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR LOSS OF VEHICLE, CARGO OR PROFITS.



## CARGO SYSTEMS DIVISION HEADQUARTERS

Ancra Cincinnati  
2685 Circleport Drive, Erlanger, KY 41018  
Phone: 1-859-371-7272  
Phone Toll Free (U.S.): 1-800-233-5138  
Phone Toll Free (Canada): 1-800-929-2627  
Fax: 1-859-371-4367  
Fax Toll Free: 1-800-347-2627  
E-mail: cargo-sales@ancra.com


## LITERATURE ON REQUEST



### 220 Catalog

#### Full Line Cargo Control

Announcing the new 220 catalog of Ancra's full line of cargo control products ranging from flatbed, to interior van, to hardware and an expanded line of specialty products. The 112 page catalog covers products for your securement needs.



### Ancra Lift-A-Deck II Decking Systems

Updated Lift-A-Deck II Brochure reflects the vastly expanded product offering and explosive growth of this line for the company. This system optimizes the cargo space in vans, trucks, and trailers, increasing the payload - and revenue - for each load.

**Distributed by:**

