## Interchanges

Grote Part Number	Industy Standard Bulb Number	Color	Wattage	Bulb Cross Reference	Applications		
94751-4	194	White	1.2W	194, W5W, W3W, 147, 152, 158, 159, 161, 168, 184, 192, 259, 280, 285, 447, 464, 501, 555, 558, 585, 655, 656, 657, 1250, 1251, 1252, 2450, 2652, 2821, 2921, 2825	Side marker, dome light, step light, trunk light, glove box, side repeater, license plate light		
94752-4		Red					
94753-4	194NA	Amber					
94791-4	1156	White	4.8W	1156, 1073, 1093, 1129, 1141, 1159, 1295, 1459, 1619, 1651, 1680, 7506, 7527, 1195, 3296, 3497, Ba15s	Front/rear turn signal, tail light, brake light, reverse light		
94793-4	1156NA	Amber					
94811-4	1157	White	4.8W	1157, 1016, 1034, 1075, 1130, 1154, 1158, 1493, 2057, 2357, 2397, 7528, P21, Bay15d	Front/rear turn signal, tail light, brake light		
94812-4		Red					
94831-4	3156	White	4.8W	3156, 3456, 4156	Front/rear turn signal, tail light, brake light, reverse light		
94851-4	3157	White	4.8W	3157, 3047, 3057, 3155, 3357, 3454, 3457, 3757, 4057, 4114, 4157	Front/rear turn signal, tail light, brake light		
94852-4		Red					
94853-4	3157NA	Amber					
94881-4	7440	White	4.8W	7440, 7441, 992	Front/rear turn signal, tail light, brake light, reverse light		
94891-4	7443	White	4.8W	7443, 7444	Front/rear turn signal, tail light, brake light		
94871-5	3175	White	1.44W	3175, 3022, 3021, 6428, 6430, 7065	Step light, dome light, map light, license plate ligh		
94781-5	212	White	1.44W	212, 212-2, 214-2, 6413, 6429, 4410, 560, 577, 578, 6411, 6476	Step light, dome light, map light, license plate lig		
94761-5	194	White	2W	194, W5W, W3W, 147, 152, 158, 159, 161, 168, 184, 192, 259, 280, 285, 447, 464, 501, 555, 558, 585, 655, 656, 657, 1250, 1251, 1252, 2450, 2652, 2821, 2921, 2825	Side marker, dome light, step light, trunk light, glove box, side repeater, license plate light		
94801-5	1156	White	16W	1156, 1073, 1093, 1129, 1141, 1159, 1295, 1459, 1619, 1651, 1680, 7506, 7527, 1195, 3296, 3497, Ba15s	Front/rear turn signal, tail light, brake light, reverse light		
94821-5	1157	White	16W	1157, 1016, 1034, 1075, 1130, 1154, 1158, 1493, 2057, 2357, 2397, 7528, P21, Bay15d	Front/rear turn signal, tail light, brake light		
94820-5	1	White/Amber					
94841-5	3156	White	16W	3156, 3456, 4156	Front/rear turn signal, tail light, brake light, reverse light		
94861-5	3157	White	16W	3157, 3047, 3057, 3155, 3357, 3454, 3457, 3757, 4057, 4114, 4157	Front/rear turn signal, tail light, brake light		
94860-5		White/Amber					
94771-5	211	White	2W	211, 211-2	Step light, dome light, map light, license plate ligh		
94900-5	N/A	N/A	N/A	N/A	Prevent "bulb out" error messages for certain applications		

# **Grote LED Bulb Replacements**

**STEP UP TO THE EFFICIENCY AND RELIABILITY OF LED LIGHTING** 



Grote Industries, Inc. 2600 Lanier Drive Madison, Indiana 47250 USA Phone: 812-273-1296 Phone: 800-628-0809 Fax: 812-265-8440 Email: safety@grote.com

56-9513-08

#### grote.com

Grote Industries, Co. 230 Travail Road

Phone: 905-209-9744

Phone: 800-268-5612

Fax: 905-209-9757

Fax: 800-267-9024

Canada

S. de R.L. de C.V. Markham, Ontario L3S 3J1 Ave. Rogelio González Caballero 225 Apodaca, Nuevo León México Código Postal 66600 Email: canada@grote.com Phone: +(52) 818262-4412 Fax: +(52) 818262-4404 Email: mexico@grote.com

Grote Comercial Latinoamérica

#### Grote Industries Europe GmbH William-Grote-Weg 1 D-94327 Bogen Germany Parque Industrial Stiva Aeropuerto Phone: +49 9422 40331-0 Email: europe@grote.com

Grote (Shanghai) Vehicle Lighting Systems Co., Ltd. 485 Xin Run Road, Xinqiao Township, Song Jiang, Shanghai, China 201612 Phone: +86.21.5774.9633 Email: asia@grote.com







### Replacement LED Bulbs Available for Most Popular 12V Lighting Applications

Replace your standard incandescent light bulbs with Grote's LED bulbs and you may never have to replace them again. Perfect for interior courtesy lights or exterior lights for "Off-Road" or "Show Vehicle" usage.



### **Try Me Feature**

- "Place anywhere" merchandising display includes innovative solar powered "Try Me" feature.
- Each individual LED bulb package has socket and metal contacts.
- Touch the back of the package to the header and press the button to see one bulb illuminated.

# **Grote Program Advantages**

Grote Program Advantages	Grote	Sylvania	Philips	Pilot	Putco	Street Glow	Jam Strait
Complete LED program, including ultra-high brightness and high brightness offerings	х				х	х	х
40-50% more LEDs per bulb in most applications. More LEDs = brighter bulbs	х						
High power bulbs feature LEDs from leading LED manufacturer	Х	х	Х		Х		
Packaging with smallest footprint possible maximizes space for more SKUs	Х					Х	
Innovative display packaging utilizing "Try Me" feature with solar technology	Х						
Environmentally friendly product packaging– no batteries inside	х	х	Х		х	х	х
From the leader in Automotive LED innovation	Х						
"Load Equalizer" technology. Bulbs will not cause "bulb out" error in most applications	х			Х			х
Best value product for consumer	Х						

### **CANbus Load Equalizer**

- CANbus is a vehicle communication standard designed to allow microcontrollers and devices to communicate with each other within a vehicle, without a host computer.
- A vehicle's bulb detection system uses current draw to determine if a bulb is functioning. The vehicle's on-board computer reads that the current used was below the normal threshold and triggers a "bulb out" warning. Halogen bulbs draw up to 1A of current. Equivalent LED draws only 0.30A.
- Current draw threshold levels vary between manufacturers, models, and even model years.



#### **"BULB OUT" WARNING SOLUTION**

- Various vehicles were tested to determine the current draw threshold. It was determined that the "average" threshold is 0.65A of current draw at 13.8V.
- The test concluded that a bulb with 0.50-0.52A was the maximum allowable amount of current draw without compromising the life of the LEDs. This design is now exclusively on these bulbs.
- In the event that a vehicle's current draw threshold is higher than that of the LED bulb, a Load Equalizer will need to be used.
- Grote provides a Load Equalizer that creates a 2.5A draw on the circuit, which is higher than the current draw of any halogen mini bulb. The addition of the Load Equalizer will completely eliminate the "bulb out" warning.

### **"BULB OUT" TECHNOLOGY IS AVAILABLE ON THE FOLLOWING BULBS:**

• 94791-4	• 94812-4	• 94852-4	• 94881-4
• 94793-4	• 94831-4	• 94853-4	• 94891-4

- 94/93-4 94031-4 • 04011 4 • 04051 4
- 94811-4 94851-4