



TRUCK / TRAILER LIFT AXLE Specification Sheet

- CONTACT NAME: _____ COMPANY: _____
- PHONE: _____ FAX _____ DATE: _____
- STEER: _____ NON-STEER _____
- TRUCK or TRAILER: _____ Roll-off: _____ Yes / No _____
- All truck mount suspension are bolt-on and without drilled holes
- IF TRAILER BOLT ON or WELD ON: _____
- LIFT AXLE CAPACITY: _____
- VEHICLE'S PRIMARY SUSPENSION STYLE: _____
E.g. (AIR, LEAF SPRING, RUBBER BLOCK, CAMEL BACK, CHALMERS)
- SINGLE OR TANDEN AXLE: _____ UNLOADED _____ LOADED _____
- BOTTOM OF FRAME TO GROUND: UNLOADED _____ LOADED _____
- SPECIFIC SIZE OF LIFT AXLE TIRE (255/70R22.5) OR LOADED TIRE RADIUS: _____
Tire size is for ride height calculations, tires and rims are not supplied.
- PUSHER (in front of drive) OR TAG (behind drive): _____
- IF PUSHER: BOTTOM OF FRAME TO BOTTOM OF DRIVESHAFT: _____
○ OR drive shaft to ground dimension: _____
- HUB & DRUM OPTION HUB PILOT or STUD PILOT: _____
- FRAME WIDTH: OUTSIDE TO OUTSIDE OR TRAILER BEAM CENTERS: _____
- PRE-PLUMBED (if available) YES / NO SLACKS YES / NO CHAMBERS YES / NO
- AIR KIT YES / NO, IF YES INSIDE or OUTSIDE IF OUTSIDE COMPOSITE or STAINLESS

FOR HENDRICKSON USE ONLY. Do not complete below this line.

HENDRICKSON AUXILIARY AXLE SYSTEMS

PHONE: 800-660-2829 or 740-929-5600

FAX: 740-929-5601

Judy Gallagher 800-660-2829 x5644 or 740-929-5644